

Dysetabel for Nelson SR150 kanon, 21°:

Tal hentet fra www.nelsonirrigation.com

Tryk (Bar)	18mm		19mm		20mm		21mm		22mm		23mm		24mm	
	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)
3,5	20,2	36,5	22,7	38,0	25,4	39,0	28,0	4,0	30,9	41,5	34,1	42,5	37,5	44,0
4,0	21,6	38,0	24,3	39,0	27,1	40,5	29,9	41,5	33,0	43,0	36,4	44,0	40,1	45,5
4,5	22,9	39,0	25,7	40,5	28,7	41,5	31,7	43,0	35,0	44,5	38,6	46,0	42,5	47,0
5,0	24,2	40,0	27,1	41,5	30,3	43,0	33,4	44,5	36,9	46,0	40,7	47,0	44,8	48,5
5,5	25,3	41,5	28,5	43,0	31,7	44,0	35,1	45,5	38,7	47,0	42,6	48,5	47,0	50,0
6,0	26,5	42,5	29,8	44,0	33,1	45,5	36,6	47,0	40,4	48,5	44,5	50,0	49,0	51,5

Tryk (Bar)	25mm		26mm		27mm		28mm		29mm		30mm		31mm	
	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)
3,5	41,0	45,0	44,8	46,0	49,0	47,5	53,3	48,5	57,9	50,0	62,8	51,0	67,8	52,0
4,0	43,8	46,5	47,8	48,0	52,3	49,0	57,0	50,5	61,9	52,0	67,1	53,0	72,5	54,0
4,5	46,5	48,5	50,7	49,5	55,5	51,0	60,5	52,0	65,7	53,5	71,2	54,5	76,9	56,0
5,0	49,0	50,0	53,5	51,0	58,5	52,5	63,8	54,0	69,2	55,0	75,1	56,5	81,1	57,5
5,5	51,4	51,0	56,1	52,5	61,4	54,0	66,9	55,5	72,6	57,0	78,7	58,0	85,0	59,5
6,0	53,7	52,5	58,6	54,0	64,1	55,5	69,9	56,5	75,8	58,0	82,2	59,5	88,8	61,0

Tryk (Bar)	32mm		33mm		34mm	
	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)	m ³ /h	Rad.(m)
3,5	73,1	53,0	78,7	54,0	84,5	55,0
4,0	78,1	55,0	84,2	56,0	90,3	57,0
4,5	82,9	57,0	89,3	58,0	95,8	59,0
5,0	87,4	59,0	94,1	60,0	101,0	60,5
5,5	91,6	60,5	97,8	61,5	105,9	62,5
6,0	95,7	62,0	103,0	63,0	110,6	64,0

